

**Great Plains Industries, Inc.**

5252 E. 36th St. N.

Wichita, KS 67220

Tel: 888-996-3837

Fax: 316-686-6746



Email: [info@gpi.net](mailto:info@gpi.net)

Industrial Meters > G2 Series Industrial Grade Turbine Flow Meters > G2 Industrial Meters - Stainless Steel > Item # G2S07I09LMA

**Item # G2S07I09LMA G2 Industrial Meters - Stainless Steel**  
**Turbine with local display mesh**

**G2 Industrial Meters - Stainless Steel****Turbine with local display mesh**

2 Totals (1 resettable/1 cumulative), Factory calibration in gallons and liters, 2 user calibrations and flow rate

[larger image](#)[larger image](#)

[Specifications](#) · [Wetted Materials](#) · [Features and Benefits](#)

**Specifications**

<b>Fitting Type</b>	ISO (Female)
<b>Electronic Choice</b>	9
<b>Housing Material</b>	316 Stainless Steel
<b>Turbine Size</b>	3/4 Inch
<b>Flow Range</b>	2 to 20 gpm 7.6 to 75.7 lpm
<b>Accuracy (Turbine only)</b>	± 1.5 %
<b>Accuracy (Turbine with Computer)</b>	± 1.0 %
<b>Repeatability</b>	±0.1 %
<b>Pressure Rating</b>	1500 psi 102 bar
<b>Operating Temperature Range - Turbine Only</b>	-40 to 250 °F -40 to 121 °C
<b>Operating Temperature Range with Computer</b>	+14 to 140 °F -10 to 60 °C

<b>Frequency Range</b>	37 - 370 Hz at 2 - 20 GPM
<b>Recommended Strainer Size</b>	55 mesh
<b>Maximum Flow</b>	30 GPM (113.6 LPM) 30 gpm 113.6 lpm
<b>Wrench Flat Size</b>	1 5/16 Inch 33 mm
<b>Shipping Weight</b>	2.5 lbs 1.1 kg
<b>Shipping Weight with Turbine Only</b>	2.3 lbs 1 kg
<b>Meter Length</b>	4.3 Inch
<b>Meter Height ?</b>	2 Inch 51 mm
<b>Meter Width</b>	2 Inch 51 mm
<b>Packaging</b>	Turbine with Mounted Local Display Use for Turbine Only
<b>Calibration</b>	Liters / Minute
<b>Product Identifier</b>	Industrial Grade Meter

---

#### Wetted Materials

<b>Housing:</b>	316 Stainless Steel
<b>Bearings:</b>	Ceramic
<b>Shaft:</b>	Tungsten Carbide
<b>Rotor:</b>	PVDF
<b>Rings:</b>	316 Stainless Steel

---

#### Features and Benefits

- Stainless steel meters have excellent chemical compatibility.
- Modular design allows for use with Output Modules, Sensors and Remote Transmitters.
- Local Display Computer features: 2 Totals (1 Reset table, 1 Cumulative); Factory Calibration in gallons and liters; 2 User Calibrations and Flow rate.
- High accuracy meter.
- Internal parts are simple to replace for easy maintenance.
- Powered by Lithium batteries for approximately 9,000 hours.
- Accessories easily upgrade meter.

[Print](#)
[Back](#)