

**Great Plains Industries, Inc.**

5252 E. 36th St. N.

Wichita, KS 67220

**Tel:** 888-996-3837**Fax:** 316-686-6746**Email:** [info@gpi.net](mailto:info@gpi.net)

Industrial Meters > G2 Series Industrial Grade Meters > G2 Industrial Meters - PVC > Item # G2C10N09GMA

**Item # G2C10N09GMA Turbine with local display****Turbine with local display**


2 Totals (1 resettable/1 cumulative), Factory calibration in gallons and liters, 2 user calibrations and flow rate

[larger image](#)

[Specifications](#) · [Wetted Materials](#) · [Features and Benefits](#)

**Specifications**

<b>Fitting Type</b>	NPT (Female)
<b>Electronic Choice</b>	09
<b>Calibration</b>	Gallons / Minute
<b>Packaging</b>	Use for Turbine Only or Turbine with Mounted Local Display.
<b>Housing Material</b>	PVC
<b>Turbine Sizes</b>	1 Inch
<b>Flow Range</b>	5 to 50 gpm 18.9 to 190 lpm
<b>Accuracy (Turbine only)</b>	± 1.5 %
<b>Repeatability</b>	±0.3 %
<b>Pressure Rating</b>	150 psi 10.2 bar
<b>Operating Temperature Range -Turbine Only</b>	+32 to 140 °F 0 to 60 °C
<b>Operating Temperature Range with Computer</b>	+32 to 140 °F 0 to 60 °C
<b>Storage Temperature</b>	-40 to 158 °F -40 to 70 °C
<b>Typical K-Factor</b>	540
<b>Frequency Range</b>	45 - 450 Hz at 5 - 50 GPM
<b>Recommended Strainer Size</b>	28 mesh

<b>Maximum Flow</b>	75 gpm 284 lpm
<b>Shipping Weight</b>	1.9 lbs 0.8 kg
<b>Shipping Weight with Turbine Only</b>	1.7 lbs 0.77 kg
<b>Meter Length</b>	8.1 Inch 206 mm
<b>Meter Height ?</b>	3.3 Inch 84 mm
<b>Meter Width</b>	2.8 Inch 71 mm
<b>Approvals +</b>	 CE
<b>Product Identifier</b>	Industrial Grade Meter

---

#### Wetted Materials

<b>Housing:</b>	PVC
<b>Bearings:</b>	Ceramic
<b>Shaft:</b>	Ceramic
<b>Rotor:</b>	PVDF
<b>Rings:</b>	Viton

---

#### Features and Benefits

- PVC meters are economical, durable and lightweight.
- Available with Local Display or Remote Transmitter.
- Local Display Computer features: 2 Totals (1 Resettable, 1 Cumulative); Factory Calibration in gallons and liters; 2 User Calibrations and Flowrate.
- Accessories easily upgrade meter.
- One field replaceable internal part makes maintenance easy.

[Print](#) [Back](#)