



Great Plains Industries, Inc.
 5252 East 36th Street North
 Wichita, KS 67220-3205
 Telephone: 316-686-7361
 Toll Free (USA & Canada): 800-835-0113
 Fax: 316-686-6746
 Sales Email: gpisales@gplains.com

FM-200



Series		FM-200
Design		Nutating Disc
Housing		Aluminum
Fitting Size	Option 1	3/4 inch
	Option 2	1 inch
Fitting Type	Option 1	NPT
	Option 2	BSPP
Flow Range	GPM	4-20 GPM
	LPM	15-75 LPM
Accuracy	Factory Calibration (See Note 1)	+ - 2%
Operating Temperature Range		Outdoors, Year Around
Wetted Components	Housing	Aluminum
	Seals	Buna-N (Nitrile)
	Wetted Gear Train	Acetal (Delrin)
	Nutating Disc	PBT Polyester (Valox)
Strainer Size		10 mesh
Maximum Working Pressure	PSIG	50 PSIG
	bar	3.4 bar
Shipping Weight	lbs	4 lbs
	kg	1.8 kg
Approvals		UL Listed, Not Approved for Use with Aviation Fuel
Maximum Display Value Batch Total	Gallons	999.9
	Litres	9999

Maximum Display Value Cumulative Total	Gallons	99999
	Litres	999999
Note 1		Field Calibration Available