



Great Plains Industries, Inc.
 5252 East 36th Street North
 Wichita, KS 67220-3205
 Telephone: 316-686-7361
 Toll Free (USA & Canada): 800-835-0113
 Fax: 316-686-6746
 Sales Email: gpisales@gplains.com

FM-300H



Series		FM-300H
Design		Nutating Disc
Housing		PBT Polyester
Fitting Size	Option 1	1 inch
Fitting Type	Option 1	NPT
Flow Range	GPM	2-20 GPM
	LPM	7-75 LPM
Accuracy		+/-2% of reading
Repeatability		+/- .25%
Pressure Rating	PSIG	50 PSIG
	bar	3.4 bar
Operating Temperature Range	Fahrenheit	15 to 130°F
	Celsius	-9 to 54°C
Wetted Components	Housing	PBT Polyester (Valox)
	Seals	Viton
	Nutating Disc	PBT Polyester (Valox)
	Signal Generators	Ferrite (Ceramic Magnet)
Shipping Weight	lbs	3 lbs
	kg	1.4 kg
Maximum Display Value Batch Total	Gallons	999999
	Litres	999999
Maximum Display Value Cumulative Total	Gallons	999999
	Litres	999999

Power Source		9 volt alkaline battery
Electronic Features	Feature 1	2 Totals(1 Cumulative, 1 Batch)
	Feature 2	Factory Calibration in Gallons or Litres
	Feature 3	Field Calibration Available