



Great Plains Industries, Inc.
 5252 East 36th Street North
 Wichita, KS 67220-3205
 Telephone: 316-686-7361
 Toll Free (USA & Canada): 800-835-0113
 Fax: 316-686-6746
 Sales Email: gpsales@gplains.com

MD-130



Series		MD-130
Design		Nutating Disc
Housing		Aluminum
Fitting Size	Option 1	3/4 inch
	Option 2	1 inch
	Option 3	1-1/2 inch
Fitting Type	Option 1	NPT
	Option 2	BSPP
Flow Range	GPM	5-30 GPM
	LPM	19-114 LPM
Accuracy	Factory Calibration (See Note 1)	+ - 2%
Operating Temperature Range	Fahrenheit	-20 to 125°F
	Celsius	-29 to 52°C
Wetted Components	Housing	Aluminum
	Seals	Buna-N (Nitrile)
	Wetted Gear Train	Acetal (Delrin)
	Nutating Disc	PPS (Ryton)
Strainer Size		10 mesh
Maximum Working Pressure	PSIG	50 PSIG
	bar	3.4 bar
Pressure Drop		0.2 PSID @ 2 GPM(0.014 bar @ 8 LPM) 15 PSID @ 30 GPM(1.034 bar @ 120 LPM)

Shipping Weight	lbs	6 lbs
	kg	2.7 kg
Approvals		UL Listed, Not Approved for Use with Aviation Fuel
Maximum Display Value Batch Total	Gallons	999.9
	Litres	99999
Maximum Display Value Cumulative Total	Gallons	99999.9
	Litres	999999
Note 1		Field Calibration Available